

VERSALIFTVTX-2406

Chassis mounted platform



3.5-5.2t GVW



24.2m Articulated boom



FPC controls



H-Frame outriggers



Type Approved



Euro 6 compliance







Specifications			
W. I I . I .	3.5T GWW Mercedes Sprinter	3.5T GWW Iveco Daily	5.2T GWW Iveco Daily
Working height	24.2m	24.2m	24.2m
Platform height	22.2m	22.2m	22.2m
Max. outreach* at:			
80kg	12.5m	12.5m	12.5m
120kg	11.2m	11.3m	11.3m
200kg	9.0m	8.9m	8.9m
220kg	8.2m	8.3m	8.3m
Max. basket capacity	220kg	220kg	220kg
GVW	3500kg	3500kg	5200kg
Max. slope	1° / 1°	1° / 1°	1° / 1°
Payload (after driver,	Circa 15kg	Circa 15kg	Circa 1300kg
passenger and fuel)**			

Standard equipment

- Easy to use full proportional (FPC) CANbus controls with display
- Articulated boom
- Extendable H-frame outriggers to rear
- Emergency hand pump
- Two person walk-in aluminium basket (front mounted flat bottomed)
- 220kg SWL basket
- · Outreach load sensing system
- Home function
- Euro 6 compliance
- Designed to work up to 3.0m below ground level

Optional equipment

- GRP bucket (reduces outreach)
- Bespoke locker design (5T vehicles only)
- Full R&M contract available direct from the manufacturer

Key features







Ability to access below ground



The ability to work over rooftops to access difficult to reach areas is aided by a flat bottomed basket




Compact H-frame outriggers



Available on 3.5T GVW Mercedes Sprinter and 3.5T and 5.2T Iveco Daily

Diagrams



Working envelope at 80/120/200/220kg bucket SWL



Easy to use full proportional (FPC) CANbus controls with display

Notes

Technical information is subject to change without notice. Images may show optional equipment.

- *Depending on the vehicle and subject to options fitted
- **Max. payload after driver, passenger and fuel and subject to options fitted

The photographs in this brochure are for promotional purposes only. Specifications are subject to change without notice.

Revision: 01/2019



Versalift Distributors (UK) Ltd. 1 Altendiez Way, Latimer Park, Burton Latimer, Kettering. NN15 5YT

T: 01536 721010 E: sales@versalift.co.uk

F: 01536 721111 W: www.versalift.co.uk