

# **VERSALIFT**VTL-140-F

Van mounted telescopic platform





Mercedes-Benz Sprinter (3,500 kg GVW)



Available for class B driving licence



LMC controls with variable outreach



Emergency lowering controls at the pedestal



Knuckle/turret tailswing within the mirrors



Outriggers within the mirrors







### **Specifications**

































Tow bar

Inverter

**Optional equipment** 

LED ceiling lights in the van

Walk-Through-System

Bucket rotator (2 x 90°)\*\*\*\* Display in the upper control panel

Reversing camera

LMC

Workshop interior

### **Dimensions**




**Length:** 7,135 mm

**Height:** 3,490 mm


Wheelbase: 3.665 mm

# Stow guide & limited working area without outriggers Diagramme(s)



Drive option (drive the vehicle with raised platform)\*\*\*

# Working envelope



Limited working area without outriggers (optional)

Retailer

## Key features



Ground level emergency lowering from the load area (pedestal mounted valve bank)



Turret/knuckle tail swing and outriggers within the mirrors



Workshop interior (optional)



LMC (Load Moment Controls): Variable outreach and up to 2 actions at a time (1 per joystick)

# Notes

Technical information is subject to change without notice. Images may show optional equipment.

- \* Depending on the vehicle.
- \*\* Max payload with a driver, a passenger and a full tank of fuel (220 kg added to the installation weight).
- \*\*\* Requires a display in the control panel and the option "Limited working area without outriggers".
- \*\*\*\* Reduced outreach.

V934L (Versalift VTL-39-140-F on Mercedes-Benz Sprinter Van) - revision 2018/04